



## Product Information NS-C.03.03

### AVIA Marine HD 1200-15W40

<b>Description</b>	<p>This marine oil for diesel engines for marine applications, is based on top-grade solvent<sub>1</sub> refined base oils and multifunctional additives, to obtain the following properties:</p> <ul style="list-style-type: none"><li>- a strong oxidation-stability</li><li>- a stable viscosity index</li><li>- a high dependency and dispersion power</li><li>- a good alkalinity, to neutralize the acid compounds which are produced during the combustion of a distillate diesel fuel</li><li>- effective in preventing from wear, corrosion and foam</li><li>- a low pour-point</li><li>- good water-separation power</li></ul>																		
<b>Application</b>	<p>This marine oil is suitable as lubricating oil of high and medium speed marine diesel engines with or without turbo-charging and the use of distillate diesel fuel. Due to its load-carrying properties this oil can also be used in shipboard gearboxes.</p>																		
<b>Specifications</b>	<p>Performance level API CF MIL-L-2104C</p>																		
<b>Typicals</b>	<table><tr><td>Density at 15 °C, kg/l</td><td>0,885</td></tr><tr><td>Viscosity -20°C, mPa.s</td><td>6200</td></tr><tr><td>Viscosity 40 °C, mm<sup>2</sup>/s</td><td>109,40</td></tr><tr><td>Viscosity 100 °C, mm<sup>2</sup>/s</td><td>14,30</td></tr><tr><td>Viscosity Index</td><td>133</td></tr><tr><td>Flash Point COC, °C</td><td>226</td></tr><tr><td>Pour Point, °C</td><td>-33</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>12,2</td></tr><tr><td>Sulphate Ash, %</td><td>1,67</td></tr></table>	Density at 15 °C, kg/l	0,885	Viscosity -20°C, mPa.s	6200	Viscosity 40 °C, mm <sup>2</sup> /s	109,40	Viscosity 100 °C, mm <sup>2</sup> /s	14,30	Viscosity Index	133	Flash Point COC, °C	226	Pour Point, °C	-33	Total Base Number, mgKOH/g	12,2	Sulphate Ash, %	1,67
Density at 15 °C, kg/l	0,885																		
Viscosity -20°C, mPa.s	6200																		
Viscosity 40 °C, mm <sup>2</sup> /s	109,40																		
Viscosity 100 °C, mm <sup>2</sup> /s	14,30																		
Viscosity Index	133																		
Flash Point COC, °C	226																		
Pour Point, °C	-33																		
Total Base Number, mgKOH/g	12,2																		
Sulphate Ash, %	1,67																		

The above figures are typical of those obtained with normal production batch, they are not a technical specification, due to continuous development of the product, they may change.

**Packaging** 206L

**Storage** All packages should be stored under a roof. If they are stored in the open air where they can be exposed to atmospheric conditions - rain, they should be placed in a horizontal position, so as to prevent ingress of water and prevent the destruction of marking, it is best to use canvas.

### Health, Occupational Health and Safety, Environment

Safety information is included in the Safety Data Sheet (SDS Safety Data Sheet). It contains detailed information on the potential hazards, precautions and First Aid measures, together with information on the impact on the environment and the disposal of used products. UNIMOT S.A. AVIA POLSKA and cooperating companies do not take responsibility for the consequences of improper product use or non-use of the precautions. Before using the product for purposes other than those listed, please consult your local UNIMOT S.A. AVIA POLSKA office.