



Product Information NS-A.06.95

## AVIA SUPER 5W40

<b>Description</b>	<p>This motor oil is based on high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained:</p> <ul style="list-style-type: none"><li>- a high and stable viscosity index</li><li>- a fast cold start</li><li>- a strong resistance against oxidation</li><li>- a good detergency and dispersion</li><li>- a safe lubrication film at high temperatures</li><li>- a strong protection against wear, corrosion and foaming</li></ul>																		
<b>Application</b>	<p>This all-round motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.</p>																		
<b>Specifications</b>	<p>Performance level ACEA A3/B4 API SN/CF MB 229.1 VW 501.01/505.00</p>																		
<b>Typicals</b>	<table><tr><td>Density at 15 °C, kg/l</td><td>0,856</td></tr><tr><td>Viscosity -30 °C, mPa.s</td><td>5470</td></tr><tr><td>Viscosity 40 °C, mm<sup>2</sup>/s</td><td>85,20</td></tr><tr><td>Viscosity 100 °C, mm<sup>2</sup>/s</td><td>14,20</td></tr><tr><td>Viscosity Index</td><td>172</td></tr><tr><td>Flash Point COC, °C</td><td>220</td></tr><tr><td>Pour Point, °C</td><td>-39</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>10,2</td></tr><tr><td>Sulphate Ash, %</td><td>1,26</td></tr></table>	Density at 15 °C, kg/l	0,856	Viscosity -30 °C, mPa.s	5470	Viscosity 40 °C, mm <sup>2</sup> /s	85,20	Viscosity 100 °C, mm <sup>2</sup> /s	14,20	Viscosity Index	172	Flash Point COC, °C	220	Pour Point, °C	-39	Total Base Number, mgKOH/g	10,2	Sulphate Ash, %	1,26
Density at 15 °C, kg/l	0,856																		
Viscosity -30 °C, mPa.s	5470																		
Viscosity 40 °C, mm <sup>2</sup> /s	85,20																		
Viscosity 100 °C, mm <sup>2</sup> /s	14,20																		
Viscosity Index	172																		
Flash Point COC, °C	220																		
Pour Point, °C	-39																		
Total Base Number, mgKOH/g	10,2																		
Sulphate Ash, %	1,26																		
	<p>The above figures are typical of those obtained with normal production batch, they are not a technical specification, due to continuous development of the product, they may change.</p>																		
<b>Packaging</b>	<p>1l, 4l, 60l, 208l</p>																		
<b>Storage</b>	<p>All packages should be stored under a roof. If they are stored in the open air where they can be exposed to atmospheric conditions - rain, they should be placed in a horizontal position, so as to prevent ingress of water and prevent the destruction of marking, it is best to use canvas.</p>																		



Product Information NS-A.06.95

## AVIA SUPER 5W40

### Health, Occupational Health and Safety, Environment

Safety information is included in the Safety Data Sheet (SDS Safety Data Sheet). It contains detailed information on the potential hazards, precautions and First Aid measures, together with information on the impact on the environment and the disposal of used products. UNIMOT S.A. AVIA POLSKA and cooperating companies do not take responsibility for the consequences of improper product use or non-use of the precautions. Before using the product for purposes other than those listed, please consult your local UNIMOT S.A. AVIA POLSKA office.